

# varimed<sup>®</sup> Furniture for OR theatres and outpatient departments




## varimed<sup>®</sup> O OR theatre and outpatient department furniture

Plastic castors with axle and fastening pin of fasteninless steel			
	Model No.	Description E	uro
	<b>222.1650.0</b> + 360 + 064 - 095 + 460 + 460 + 095 + 460 + 095 + 095 + 095 + 005 + 095 + 005	<b>Theatre seat</b> Specially-designed upholstered seat with antistatic cover, black, height adjustment from 560 to 790 mm by means of gas spring, with foot ring release. 5-arm pedestal powder coat in grey aluminium RAL 9007 with antistatic double plastic casto of 50 mm, unbraked when loaded, circular black bumper. Safe working load: 135 kg	1 <b>.048,–</b> red rs
222.1670.0	200.0011.0	Surcharge for brake loaded castors braked when loaded, released when you come off the st	<b>43,-</b> ool.
		<b>Theatre seat</b> Specially-designed upholstered seat with antistatic cover, black, height adjustment from 560 to 790 mm by means of gas spring, with foot ring release, back rest with antistatic cover 5-arm pedestal powder coated in grey aluminium RAL 9007 with antistatic double plastic castors of 50 mm, unbraked when loaded, circular black bumper. Safe working load: 135 kg	
	200.0011.0	Surcharge for brake loaded castors braked when loaded, released when you come off the st	<b>43,-</b> ool.
		Theatre seat Saddle-shaped pad with antistatic cover, black, height adjustment from 560 to 790 mm by means of gas spring with foot ring release. 5-arm pedestal powder coated in grey aluminium RAL 9007 with antistatic double plastic castors of 50 mm, unbraked when loaded, circular black bumper. Safe working load: 135 kg	<b>1.077,-</b> g,
222.1680.0	200.0011.0	Surcharge for brake loaded castors braked when loaded, released when you come off the st	<b>43,-</b> ool.
222.1660.0	<b>222.1680.0</b> 400 560-790 560-790	Theatre seat as 222.1660.0, but with back rest with antistatic cover, black. 5-arm pedestal powder coated in grey aluminium RAL 9007 with antistatic double plastic castors of 50 mm, unbraked when loaded, circular black bumper. Safe working load: 135 kg	.341,-
	200.0011.0 460 - 460	Surcharge for brake loaded castors braked when loaded, released when you come off the st	<b>43,-</b> ool.









Description

Surgeon's stool 352,as 222.1510.0, but seat disc upholstered, antistatic cover, black. Height adjustment from 485 to 655 mm. Safe working load: 135 kg

Euro

## varimed<sup>®</sup> ( OR theatre and outpatient department furniture





### 232.4260.0 - 600 320

### Instrument serving table

843,-18/10 stainless steel frame, 18/10 stainless steel table top 600 x 400 mm, non-rotatable, height adjustable from 900 to 1,320 mm, double plastic castors diam. 50 mm, antistatic, rust-proof. Safe working load: 12 kg.





Model No.



### Description

Euro

Instrument serving table 1.141,-manually operated height adjustment from 800 – 1,200 mm. Mobile 4-arm pedestal of 18/10 stainless steel and stainless steel table, top with reflex free and disinfectant-proof surface. 4 swivel castors, 1.141,-2 of which lockable, resistant to abrasions, antistatic, diam. 75 mm, with friction bearing. Safe working load: 30 kg

232.4270.0





Hand and arm operating table C€/93/42/EEC 1.2 pedestal of 18/10 stainless steel. Table top X-ray permeable, tiltable my means of ball-and-socket-joint, with clamping lever. Manually height adjustable from 650 – 950 mm. 4 swivel castors, 1.218,lockable, resistant to abrasions, antistatic, diam. 75 mm, with friction bearing. Safe working load: 40 kg.

### Accessories:

Upholstered pad antistatic, X-ray permeable, detachable, 450 x 450 x 30 mm.

230,-

varimed® O OR theatre and c department furnit		232.5210.0
Model No.	Description 232.5410.0	Euro
232.5210.0	<b>Instrument table</b> 18/10 SST rectangular tube frame (frame also serves as protection rail), 18/10 SST table tops 600 x 450 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 bumpers. Safe working load per shelf: 50 kg	474,-
232.5220.0	Instrument table, as 232.5210.0, but of 900 mm height.	474,-
232.5310.0	<b>Instrument table</b> 18/10 SST rectangular tube frame, two stainless steel 18/10 shelves, top shelf 650 x 500 mm covering frame, lower one as inserted plate of 600 x 450 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 Safe working load per shelf: 50 kg	<b>503,-</b> 4 bumpers.
232.5320.0	<b>Instrument table,</b> as 232.5310.0, but of 900 mm height.	503,-
232.5410.0	<b>Instrument table</b> 18/10 SST rectangular tube frame (frame also serves as protection rail), 18/10 SST table tops 700 x 600 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 bumpers. Safe working load per shelf: 50 kg	548,-
232.5420.0	<b>Instrument table,</b> as 232.5410.0, but of 900 mm height.	548,-
232.5510.0	<b>Instrument table</b> 18/10 SST rectangular tube frame, two stainless steel 18/10 shelves, top shelf 750 x 650 mm covering frame, lower one as inserted plate of 700 x 600 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 bumpers. Safe working load per shelf: 50 kg	606,-
232.5520.0	Instrument table, as 232.5510.0, but of 900 mm height.	606,-
232.5610.0	<b>Instrument table</b> 18/10 SST rectangular tube frame (frame also serves as protection rail), 18/10 SST table tops 900 x 600 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 bumpers. Safe working load per shelf: 50 kg	564,-
232.5620.0	<b>Instrument table,</b> as 232.5610.0, but of 900 mm height.	564,-
232.5710.0	<b>Instrument table</b> 18/10 SST rectangular tube frame, two stainless steel 18/10 shelves, top shelf 950 x 650 mm covering frame, lower one as inserted plate of 900 x 600 mm, detachable, table height 800 mm, 4 plastic double castors diam. 75 mm, antistatic, antirust, abrasion-proof, 2 of which lockable, with 4 Safe working load per shelf: 50 kg	·
232.5720.0 1	<b>Instrument table,</b> as 232.5710.0, but of 900 mm height.	659,-

Plastic castors With azle and Vitastening pin of Issentess steel Standess steel S			nermostat		
242.1250.0 - <b>→</b> <sup>[0 320]</sup>	← Bowl stand 18/10 stainless steel frame, or plastic double castors diam. 5	ne 18/10 SST bowl, capacity 6 l, 0 mm, antistatic, rust-proof, height 815 mm, <b>disassembled.</b>	Euro <b>322,-</b>		
200.3070.0	Bis Accessories: Bowl, 18/10 stainless steel (€	extra).	78,-		
242.1350.0	Bowl stand 18/10 stainless steel frame, tw plastic double castors diam. 5	Bowl stand421,-18/10 stainless steel frame, two 18/10 SST bowls, capacity 6 l ea., plastic double castors diam. 50 mm, antistatic, rust-proof, height 815 mm, disassembled.421,-			
200.3070.0	Accessories: Bowl, 18/10 stainless steel (e	extra).	78,-		
242.1310.0	for heating of physiological so max. 60° C, with safety therm 5-arm base of stainless steel, rust-proof, with brake, 3 of w Voltage: 230 V, 50 Hz, 400 V	C aline solutions, adjustment knob to switch the temperature from 3 ostat and scale reading. Teflon-coated heating plate for easy cl height adjustable by servo-assisted gas cylinders; plastic castors hich antistatic, SST bowl with litre-scale, capacity 5 I. Earth conta V, connection cable with EPR (earth potential rise) protection, 5 m	eaning. diam. 75 mm, ict.		
200.5600.0 200.5610.0	Accessories: 5 L Bowl, stainless steel 18/ Fastening ring, for aseption		138,- 78,-		
	Importante For roa	some of caloby			

# All prices are subject to change and do not include VAT. Important: For reasons of safety only use original bowls from Schmitz.

## varimed<sup>®</sup> O OR theatre and outpatient department furniture



Model No.		Description	Euro
242.2350.0		<b>Drip-feed stand</b> CE/93/42/EEC 18/10 stainless steel frame, disassembled, 5-arm base, upper section with 4 hooks, drip glass, double plastic castors diam. 50 mm, antistatic, rust-proof; height adjustment from 1,300 to 2,120 mm, one-hand action. Safe working load: 2 kg (per hook).	325,-
251.1010.0 251.1030.0 251.1040.0	600 300 240 120	<b>Step</b> 18/10 stainless steel frame, fine-ribbed anti-slip tread in 18/10 stainless steel, floor pads antistatic, tread height 240 mm. <b>Step</b> , as 251.1010.0, but tread height 120 mm. <b>Step</b> , as 251.1010.0, but tread height 300 mm. Safe working load: 185 kg	247,- 243,- 250,-
251.1020.0		<b>Step</b> 18/10 stainless steel frame, fine-ribbed anti-slip treads in 18/10 stainless steel, floor pads antistatic. Safe working load: 185 kg	439,-
252.1180.0	780	<b>Refuse bucket</b> removable 12   bucket in 18/10 stainless steel, 18/10 stainless steel frame with profiled plastic wrap-around bumper, double plastic castors diam. 50 mm, antistatic, rust-proof; frame height 230 mm.	417,-
252.1190.0	→Ø 450→	<b>Refuse bucket</b> as 252.1180.0 above, with pushing handle in 18/10 stainless steel.	449,-
200.1370.0 200.1350.0		Accessories: Bucket lid in 18/10 stainless steel. 12 L Bucket in 18/10 stainless steel (extra).	80,- 115,-

### varimed<sup>®</sup> O OR theatre and outpatient department furniture Accessories Material description

Model No.	Description	Euro	Model No.	Description	Euro	Model No.	Description	Euro
<b>200.3070.0</b> 320 130 130	<b>Bowl</b> for bowl stands 242.1250.0 and 242.135 18/10 SST, diam. of 320 mm, depth of 130 mm.	<b>78,–</b> 50.0,	<b>200.1350.0</b> Ø 310	<b>12 L Bucket</b> SST 18/10 for 252.1180.0 - 252.1190	<b>115,-</b> ).0.		Lid for 12 I. bucket, 18/10 SST.	80,-
200.5610.0	<b>Fastening ring</b> for aseptic cover for 242.1310.0.	<b>78,-</b>	<b>200.4110.0</b>	<b>Pad</b> antistatic, X-ray permu for hand and arm op table 232.4460.0.	<b>230,–</b> eable, erating	200.5600.0	<b>Bowl</b> stainless steel 18/10, with litre-scale for 242.	<b>138,–</b> 1310.0.

**Material description** Frames in SST 18/10, round or rectangular tubing, electropolished. Stainless steel tops as well as claddings are of ground, brushed finish (grain size 180). All castors are resistant to abrasions. Seat upholsteries of top quality, hardwearing foam rubber with antistatic black cover.



### SCHMITZ u. Söhne GmbH & Co. KG

P. O. Box 14 61 58734 Wickede (Ruhr) Germany (postal address) Zum Ostenfeld 29 58739 Wickede (Ruhr) Germany (visiting address) T +49 (0)2377 84 0 F +49 (0)2377 84 135 www.schmitz-soehne.com export@schmitz-soehne.de

Technical service, hotline: T +49 (0)2377 84 549 F +49 (0)2377 84 210 service@schmitz-soehne.de

All articles including corresponding accessories marked with the CE label meet the standards for medical devices acc. to MPG and the EC regulation 93/42/EEC.




The products may only be used for their intended purpose of use. Please also observe our operating manual!



f/schmitz.soehne




Information on our establishments worldwide can be found on our website.



OPX mobilis<sup>®</sup> Operating Tables for Outpatient Departments and Operating Theatres Unique Flexibility and Reliability





Our goods and services are to be understood ex works. Deliveries are effected via our authorized partners or branch offices. The company reserves the right to alter the design, construction, dimensions and finish of its products without notice. All relevant dimensions and weights are to be understood as approximate information/data. Due to technical reasons colour deviations are possible. The articles shown in this catalogue are not authorized for sale in the United States. SCHMITZ Catalogue with prices No. 80, 01.2018 GB Nominal charge 3.00 Euro.